

ACCESS B400



Convenient Slitting

TECHNICAL DATA AND SPECIFICATIONS: FRAMA LETTER OPENER ACCESS B400

Opening technique	One and only desk-top letter opener world-wide, which slits letters up to 10 mm thick instead of cutting them. Hence, no risk of damaged letter contents and no bothersome disposal of cutting waste. No tangling of paper scraps in the opening mechanism.
Opening speed	Up to 400 letters per minute dependent on letter formats and weights.
Letter thickness	Automatic adjustment to all letter thicknesses up to 10 mm.
Processable formats	All formats up to C6 / B5 mixed (separate opening of large-sized envelopes C4 / B4).
Stack height	Up to 8 cm for all formats inclusively C4 / B4
Feed table	Large-sized feed surface of 26 x 22 cm
Feed mechanism	Very fast automatic start / stop function (< 1 sec.) Special auto-reverse function for the rejection of too thick letters.
Multiple-side opening	In two work steps, envelopes of all formats can be opened on both long sides, plus in a further step on one short side by using the up-foldable letter guide (up to format C5 / C6 only).
Noise level	Quiet in operation: LPA 1 m: 61.9 dB(A)
Mains connection	Power input: 100-240 VAC, 50/60 Hz Power output: 24 VDC, 5.0 A, 120 W max Maximal power consumption in operation: 80 W
Housing colour	Light grey RAL 7035 (main colour) / anthracite RAL 7016
Dimensions (L x D x H)	Letter opener: 424 x 291 x 190 mm Collecting tray: 322 x 267 x 148 mm
Net weight	5.3 kg without / 6.2 kg with collecting tray
Certificates	CE, CB

Frama AG Switzerland 1019787 R02.01 / 12.16 Information provided are subject to change

Frama AG · Dorfstrasse 6 · 3438 Lauperswil · Switzerland · T +41 34 496 98 98 · frama.com

integrity in communication.