

## INSTALLATION OF INK-JET CASSETTE MATRIX F22

### 1. Installation of Ink-Jet Cassette



Attention! Confirm the question on the screen after the insertion of the new Ink-Jet Cassette.

### 6. Close the flap



Close the flap.

### 2. Open the flap




Open the flap of the Ink-Jet Cassette.

### 7. New Ink-Jet Cassette installed




Confirm the question on the screen with „YES“.

### 3. Prepare the new Ink-Jet Cassette



Remove the two protector strips of the new Ink-Jet Cassette being careful not to touch the gold coloured contact points.

### 8. Calibration of Ink-Jet Cassette




The Ink-Jet Cassette will be calibrated.

### 4. Insert the new Ink-Jet Cassette




Insert the new Ink-Jet Cassette by pinching the grips of the new cassette and pushing it in to the franking machine.

### 9. Perform a Test Print




To perform a Test Print, insert a letter to produce an alignment Test Print.

### 5. Final check



Release the grips and check whether the locking pins are correctly positioned (see picture).


### 10. Test Print



The Test Print shows current settings. The arrows should point to where the lines appear straightest.


Example:  
Actual: X=-3 / Y=1  
Should be: X=0 / Y=2

### 11. Print Alignment X




Move to setting 0 (for example) with the - and + keys. Confirm entry with "ENTER".

### 12. Print Alignment Y



Move to setting 2 (for example) with the - and + keys. Confirm entry with "ENTER".

### 13. Repeat the Test Print



Repeat the Test Print.

### 14. Confirm



If the Test Print is correct, press "YES" to confirm the settings. Otherwise press "NO" to repeat.